

SAINT ANDREWS EPISCOPAL CHURCH

Stillwater, Oklahoma

organ by

ROY REDMAN

Opusl8

1978

Great:	2 ^{1/2} " wind pressure		
8'	Rohrflöte	61 pipes	12 wood and 49 50% tin
8'	Principal	61 pipes	90% tin in facade
4'	Octave	61 pipes	50% tin
2'	Blockflöte	61 pipes	50% tin
1 ^{1/3} ,	Mixture IV	244 pipes	75% tin
8'	Trompete	61 pipes	50% tin
Swell:	2" wind pressure		
8'	Holzgedackt	61 pipes	wood
8'	Salicional	61 pipes	12 zinc and 49 50% tin
4'	Holzflöte	61 pipes	wood
2'	Principal	61 pipes	75% tin
2 ^{2/3} ,	Quinte	61 pipes	50% tin
1 ^{3/5} ,	Terz	61 pipes	50% tin
8'	Krummhorn	61 pipes	50% tin
	Tremulant		
Pedal:	3' wind pressure		
16'	Subbass	32 pipes	wood
8'	Principal	32 pipes	18 zinc and 14 50% tin
4'	Octave	32 pipes	6 zinc and 26 50% tin
16'	Fagott	32 pipes	50% tin

Total: 17 stops 20 ranks 1104 pipes

Couplers: Swell-Great, Swell-Pedal, Great-Pedal

Mechanical key and stop action, mechanically operated swell shades

Four fixed combination pedals

Mechanical general cancel pedal

Free standing case of white oak

Ebony naturals and stop knobs, ivory topped sharps

Designed by Roy Redman based on a series of hexagonal towers arranged in a rear gallery corner.